

# Wall mounted unit

FTXTM-R + RXTM-R



BLUEEVOLUTION *perfera*



Guaranteed operation down to -25°C



Fireplace logic



Heat boost



Onecta app



Silver allergen removal and air purifying filter

## Attractive, wall mounted design with perfect indoor air quality down to -25°C

- › Guaranteed heating capacity down to -25°C
- › Seasonal efficiency values up to A+++ in cooling and heating
- › Even temperature distribution thanks to fireplace logic
- › Heat boost: fast heating during start-up (pair only)
- › Daikin Flash Streamer technology: powerful air purification
- › Silver allergen removal and air purifying filter
- › Onecta app
- › Voice control
- › Quiet in operation: down to 19dBA sound pressure level
- › 3-D airflow: air is blown into all corners of a room
- › Sleek, unobtrusive air conditioning unit
- › Blueevolution range: lower environmental impact
- › 2 area motion detection sensor

# FTXTM-R + RXTM-R



Efficiency data		FTXTM + RXTM		30R + 30R		40R + 40R	
Cooling capacity	Min./Nom./Max.	kW		0.70 /3.00 /4.50		0.90 /4.00 /5.10	
Heating capacity	Min./Nom./Max.	kW		0.80 /3.20 /6.70		1.20 /4.00 /7.20	
Power input	Cooling	Nom.	kW	0.73		1.08	
	Heating	Nom.	kW	0.60		0.74	
Space cooling	Energy efficiency class			A++			
	Capacity	Pdesign	kW	3.00		4.00	
	SEER			7.60		7.70	
	Annual energy consumption		kWh/a	138		182	
Space heating (Average climate)	Energy efficiency class			A+++			
	Capacity	Pdesign	kW	3.00		3.80	
	SCOP/A			5.12		5.30	
	Annual energy consumption		kWh/a	821		1,003	
Current - 50Hz	Maximum fuse amps (MFA)		A	16			

Indoor unit		FTXTM		30R		40R		
Dimensions	Unit	HeightxWidthxDPTH		mm		295 x778 x272		
Weight	Unit			kg		10.0		
Air filter	Type				Removable / washable			
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/ High	m <sup>3</sup> /min	4.1 /5.3 /7.8 /12.2		4.6 /5.8 /9.5 /15.4	
		Heating	Silent operation/ Low/Medium/ High	m <sup>3</sup> /min	4.0 /4.9 /7.5 /12.5		5.9 /7.1 /10.5 /17.5	
Sound power level	Cooling			dB(A)	60.0			
	Heating			dB(A)	61.0			
Sound pressure level	Cooling	Silent operation/Low/High		dB(A)	21.0 /25.0 /45.0		20.0 /24.0 /46.0	
	Heating	Silent operation/Low/High		dB(A)	19.0 /22.0 /45.0		19.0 /22.0 /46.0	
Control systems	Infrared remote control				ARC466A75			
	Wired remote control				BRC073A1			
Piping connections	Drain				18			

Outdoor unit		RXTM		30R		40R		
Dimensions	Unit	HeightxWidthxDPTH		mm		551 x763 x312		
Weight	Unit			kg		38		
Sound power level	Cooling			dB(A)	-			
Sound pressure level	Cooling	Low/Nom./High		dB(A)	-/48 /-			
	Heating	Low/Nom./High		dB(A)	-/49 /-			
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10 ~46			
	Heating	Ambient	Min.~Max.	°CWB	-25 ~18			
Refrigerant	Type				R-32			
	GWP				675			
	Charge		kg/TCO2Eq		1.1 /0.74			
Piping connections	Liquid - Gas	Type		Flare connection - Flare connection				
	Piping length	OU - IU	Max.	m	20			
	Piping length				-			
	Level difference		IU - OU	Max.	m	15		
Power supply	Phase/Frequency/Voltage				Hz/V		1~/50 /220-240	

Daikin Europe Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · <https://www.daikin.eu> · RPR Oostende (Responsible Editor)



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: [www.eurovent-certification.com](http://www.eurovent-certification.com)

ECPEN22-064

08/2022



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.