

Water cooled screw inverter chiller, standard efficiency, standard sound

- › Optimized energy efficiency both at full and part load conditions
- › Compact footprint through stacked heat exchanger lay-out
- › Heat pump version with reversibility on water side (up to 65°C hot water production)
- › Multiple options available: sound proof cabinet, rapid restart, removable electrical panel, etc. to adapt the unit to your specific application and need
- › Thanks to a large operating envelope, the unit is suitable for all possible process and comfort applications
- › High efficient flooded type heat exchanger allowing maximum unit performances
- › One or two truly independent refrigerant circuits for outstanding reliability



Cooling only/Heating only				EWWD-VZSS															
				600	700	760	890	C10	C12	C13	C14	C16	C17	C19	C21				
Space cooling	A Condition (35°C) Pdc			kW		609.91	704.22	756.52	894.23	1,039.49	1,173.02	1,288.02	1,381.01	1,552.02	1,722.02	1,875.55	2,051.2		
	ηs,c			%		340		337.2	331.6	332	337.2	331.6	331.2	320.8	338.8	322	338.8		
SEER						8.7		8.63	8.49	8.5	8.63	8.49	8.48	8.22	8.67	8.25	8.67		
Cooling capacity	Nom.			kW		610	704	757	894	1,039	1,173	1,288	1,381	1,552	1,722	1,876	2,051		
Power input	Cooling			Nom.		kW		110	132	142	162	196	231	252	276	315	339	380	404
	Capacity control				Method		Variable												
				Minimum capacity		%		20					10						
EER						5.5	5.31	5.3	5.52	5.29	5.07	5.11	5	4.93	5.08	4.93	5.08		
ESEER						7.62	7.5	7.63	7.54	7.52	7.86	7.81	7.9	7.46	7.99	7.49	7.95		
IPLV						9.43	9.36	9.4	9.37	9.4	9.52	9.56	9.57	9.36	9.7	9.38	9.65		
Dimensions	Unit	Height		mm		2,123		2,292	2,487	2,296			2,350	2,338	2,498				
		Width		mm		1,178	1,179		1,233	1,303	1,484		1,487	1,484	1,580	1,627	1,753		
		Depth		mm		3,722	3,750		3,690	3,822	4,792			4,508		4,750			
Weight	Unit			kg		2,892	2,928	2,941	3,451	4,237	5,570	5,790	5,820	6,220	6,890	7,260	8,260		
	Operation weight			kg		2,977	3,033	3,053	3,611	4,488	5,980	6,220	6,290	6,690	7,480	7,830	9,070		
Water heat exchanger - evaporator	Type			Flooded shell and tube															
	Water volume			l		88		96	134	156	230		270		320		380		
	Water flow rate	Cooling		Nom.		l/s		29.2	33.8	36.3	42.9	49.9	56.2	61.7	66.1	74.4	82.5	89.9	98.2
		Cooling		Nom.		kPa		79	106	88	98	102	69	84	70	89	78	92	80
Water heat exchanger - condenser	Type			Shell and tube															
	Water volume			l		81	102		126	217	180		200		270	250	430		
	Water flow rate	Cooling		Nom.		l/s		35.3	41	44.1	51.9	60.6	69.1	75.8	81.5	91.9	101	111	120
		Cooling		Nom.		kPa		31	29	33	29	33	44	39	45	66	42	55	37
Compressor	Type			Driven vapour compressor															
	Quantity					1					2								
Sound power level	Cooling		Nom.		dBA		101.0	105.0		107.0	106.0		107.0		108.0		110.0		
	Cooling		Nom.		dBA		82.0	86.0		88.0	87.0		88.0		89.0		90.0		
Operation range	Evaporator	Cooling		Min.~Max.		°CDB		-3~-20											
		Condenser	Cooling		Min.~Max.		°CDB		16~63										
Refrigerant	Type/GWP			R-134a/1,430															
	Charge			kg		100	110		170	180	250	260	290		320		350		
	Circuits		Quantity		1					2									
Piping connections				mm		139.7		168.3		219.1									
	Condenser water inlet/outlet (OD)					168.3mm		219.1mm		168.3 / 168.3 mm			219.1 / 219.1 mm						
Unit	Starting current		Max		A		179	214	245	295	344		-						
	Running current	Cooling		Nom.		A		171	202	220	249	300	349	379	414	470	508	566	604
		current		Max		A		256	306	350	421	491	553	555	612	727	810	926	1,009
Power supply	Phase/Frequency/Voltage			Hz/V		3~/50/400													