

Wall mounted unit

Wall mounted unit providing high efficiency and comfort down to -25°C

- › Guaranteed heating capacity at low ambient temperature, down to -25°C
- › The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation
- › Seasonal efficiency values: full range A++ in cooling and heating
- › Onecta app: control your indoor from any location with an app, via your local network or internet.
- › Voice command via Amazon Alexa or Google Assistant to control main functions such as set point, operation mode, fan speed, etc
- › Space saving contemporary wall mounted design
- › Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency
- › 3-D air flow combines vertical and horizontal auto swing to circulate a stream of warm or cool air right to the corners of even large spaces



More details and final information can be found by scanning or clicking the QR codes.



FTXTP-M



RXTP-R

Efficiency data				FTXTP + RXTP	25M + 25R	35M + 35R
Cooling capacity	Min./Nom./Max.		kW	0.80/2.50/4.00	0.80/3.50/4.40	
Heating capacity	Min./Nom./Max.		kW	1.20/3.20/6.20	1.20/4.00/6.70	
Power input	Cooling	Nom.	kW	0.57	0.92	
	Heating	Nom.	kW	0.65	0.90	
Space cooling	Energy efficiency class			A++		
	Capacity	Pdesign	kW	2.50	3.50	
	SEER			7.10	7.20	
	Annual energy consumption		kWh/a	123	170	
Space heating (Average climate)	Energy efficiency class			A++		
	Capacity	Pdesign	kW	2.50	3.00	
	SCOP/A			4.93	4.81	
	Annual energy consumption		kWh/a	710	873	
Space heating (Cold climate)	Energy efficiency class			A		
	Capacity	Pdesignh	kW	3.65	4.38	
	Annual energy consumption		kWh/a	1,941	2,394	
	SCOP/C			3.95	3.84	
Nominal efficiency	EER			4.40	3.80	
	COP			4.95	4.44	
	Annual energy consumption		kWh	284	461	
	Energy labeling Directive	Cooling/Heating		A/A		

Indoor unit				FTXTP	25M	35M
Dimensions	Unit	HeightxWidthxDepth		mm	286x770x225	
Weight	Unit			kg	9.00	
Air filter	Type				Removable/washable	
Fan	Air flow rate	Cooling	Silent operation/Low/Medium/High	m³/min	3.9/5.5/8.3/11.5	
		Heating	Silent operation/Low/Medium/High	m³/min	4.5/5.6/8.7/11.5	
Sound power level	Cooling			dBA	58	
	Heating			dBA	58	
Sound pressure level	Cooling	Silent operation/Low/High		dBA	21/26/43	
	Heating	Silent operation/Low/High		dBA	21/26/43	
Control systems	Infrared remote control				ARC480A53	

Outdoor unit				RXTP	25R	35R
Dimensions	Unit	HeightxWidthxDepth		mm	551x763x312	
Weight	Unit			kg	38	
Sound power level	Cooling	Nom.		dBA	61.0	
	Heating	Nom.		dBA	61.0	
Sound pressure level	Cooling	Nom.		dBA	48	
	Heating	Nom.		dBA	49	
Operation range	Cooling	Ambient	Min.-Max.	°CDB	-10~46	
	Heating	Ambient	Min.-Max.	°CWB	-25~-18	
Refrigerant	Type				R-32	
	GWP				675	
	Charge			kg/CO2Eq	1.1/0.75	
Piping connections	Liquid	OD		mm	6.35	
	Gas	OD		mm	9.50	
	Piping length	OU - IU	Max.	m	20	
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m	15	
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50 /220-240		
Current - 50Hz	Maximum fuse amps (MFA)		A	16		

Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for operation range | See separate drawing for electrical data | Cooling: indoor temp. 27°CDB, 19.0°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal) | Contains fluorinated greenhouse gases