

Concealed flexi type unit

AC fan motor unit for horizontal or vertical concealed mounting

- › Quick fixing system for wall or ceiling mounted installation
- › Pre-assembled 3-way/4-port on/off valves are available
- › Valve packages are insulated, no extra drain pan required
- › Valve packages contain balancing valves and sensor pocket
- › Fast-on connections for electrical options: no tools needed
- › The air filter can easily be removed for cleaning
- › Electric heater: no relay up to 2kW capacity
- › Electric heater: equipped with two overheat cut-out thermostats
- › Available static pressure up to 50Pa at maximum speed



Indoor unit			FWM-DAT/DAF	01	15	02	25	03	35	04	06	08	10	01	15	02	25	03	35	04	06	08	10				
				2-pipe										4-pipe													
Cooling capacity (standard conditions)	Total capacity	High	kW	1.50	1.69	1.91	2.36	2.87	3.45	4.23	4.41	6.53	7.78	1.42	1.64	1.74	2.32	2.81	3.36	4.16	4.57	6.46	7.64				
		Medium	kW	1.21	1.48	1.66	1.99	2.34	2.58	3.21	3.59	5.14	6.07	1.11	1.44	1.52	1.96	2.29	2.54	3.17	3.74	5.10	5.99				
		Low	kW	1.02	1.24	1.34	1.57	1.73	1.94	2.47	2.95	3.88	4.00	0.97	1.22	1.24	1.55	1.70	1.92	2.44	3.06	3.84	3.96				
	Sensible capacity	High	kW	1.16	1.25	1.37	1.82	2.05	2.69	3.05	3.55	4.73	5.72	1.10	1.22	1.41	1.79	2.01	2.61	2.99	3.47	4.67	5.61				
		Medium	kW	0.94	1.10	1.20	1.53	1.66	1.99	2.39	2.85	3.70	4.46	0.87	1.07	1.18	1.50	1.62	1.96	2.36	2.80	3.67	4.40				
Heating capacity (standard conditions)	High	kW	0.77	0.93	0.98	1.15	1.23	1.41	1.76	2.27	2.75	2.94	0.73	0.91	0.96	1.14	1.21	1.40	1.74	2.23	2.73	2.91					
	Medium	kW	1.82	1.84	2.15	2.70	2.94	4.05	4.24	4.98	6.49	8.37	1.66	1.76	2.53	2.68	4.20	3.82	4.64	6.97	7.35						
	Low	kW	1.48	1.72	1.81	2.26	2.37	3.13	3.24	4.08	5.17	6.53	1.49	1.56	2.18	2.31	3.47	3.22	4.07	6.02	6.29						
Power input	High	kW	1.21	1.45	1.50	1.74	1.76	2.39	2.47	3.31	3.97	4.39	1.31	1.36	1.78	1.88	2.82	2.73	3.55	5.02	4.85						
	Medium	kW	0.037	0.053	0.057	0.056	0.065	0.098	0.182	0.244	0.037	0.053	0.057	0.056	0.065	0.098	0.182	0.244									
	Low	kW	0.03	0.03	0.02	0.03	0.04	0.05	0.07	0.13	0.17	0.03	0.04	0.05	0.06	0.07	0.13	0.17									
Dimensions	Unit	HeightxWidthxDepth	mm	535x584x224			535x794x224			535x1,000x224			535x1,210x249			535x584x224			535x794x224			535x1,000x224			535x1,210x249		
Weight	Unit		kg	16.5	16.9	21.4	22.1	26.3	26.4	26.6	35.4	16.5	16.9	21.4	22.1	26.3	26.4	26.6	35.4								
Air filter	Type			Polypropylene net																							
Fan	Type			Centrifugal																							
	Quantity			1					2					1					2								
	Air flow rate	High	m ³ /h	319	344	442	640	706	785	1,011	1,393	307	330	327	432	431	628	690	763	998	1,362						
	Medium	m ³ /h	233	271	341	450	497	605	771	1,022	225	261	334	332	444	490	593	765	1,007								
	Low	m ³ /h	178	211	241	320	361	470	570	642	174	205	238	237	316	356	460	565	636								
Total sound power level	High	dBA	47.0	49.0	50.0	48.0	52.0	53.0	56.0	61.0	67.0	45.0	49.0	50.0	48.0	47.0	53.0	56.0	58.0	60.0	66.0						
	Medium	dBA	42.0	44.0	43.0	42.0	43.0	49.0	54.0	60.0	39.0	44.0	43.0	41.0	45.0	46.0	53.0	54.0	58.0								
	Low	dBA	37.0	38.0	40.0	35.0	36.0	35.0	43.0	47.0	49.0	33.0	40.0	38.0	34.0	33.0	36.0	39.0	48.0	46.0	48.0						
Sound pressure level	High	dBA	42.0	44.0	45.0	43.0	47.0	48.0	51.0	56.0	62.0	40.0	44.0	45.0	43.0	42.0	46.0	51.0	54.0	55.0	61.0						
	Medium	dBA	37.0	39.0	38.0	37.0	38.0	44.0	49.0	55.0	34.0	39.0	38.0	36.0	38.0	41.0	48.0	49.0	53.0								
	Low	dBA	32.0	33.0	35.0	30.0	31.0	30.0	38.0	42.0	44.0	28.0	33.0	29.0	28.0	29.0	32.0	43.0	41.0	43.0							
Electric heater	Power input (Optional)	kW	1.0	1.5	1.6	2.0	3.0	1.0	1.5	1.6	2.0	3.0															
Piping connections	Drain OD	mm	16																								
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/230																								
Control systems	Wired remote control		FWEC1A / FWEC2A / FWEC3A / FWEC5A																								

For standard conditions refer to the Measuring Conditions table, at the end of this catalogue