


# Wall mounted unit

For rooms with no false ceilings nor free floor space

- › Optimised design for R-32 refrigerant
- › Flat, stylish front panel blends easily within any interior décor and is easier to clean
- › Can easily be installed in both new and refurbishment projects
- › The air is comfortably spread up- and downwards thanks to 5 different discharge angles that can be programmed via the remote control
- › Maintenance operations can be performed easily from the front of the unit



 Access all technical information on FXAA-A at [my.daikin.eu](http://my.daikin.eu) or click here

Indoor unit		FXAQ		15A	20A	25A	32A	40A	50A	63A
Cooling capacity	Total capacity	At high fan speed	kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1
Heating capacity	Total capacity	At high fan speed	kW	1.9	2.5	3.2	4.0	5.0	6.3	8.0
Power input - 50Hz	Cooling	At high fan speed	kW	0.02		0.03		0.02	0.03	0.05
	Heating	At high fan speed	kW	0.03		0.04		0.02	0.04	0.06
Dimensions	Unit	HeightxWidthxDepth	mm	290x795x266				290x1,050x269		
Weight	Unit		kg	12				15		
Fan	Air flow rate - 50Hz	Cooling Low/High fan speed	m <sup>3</sup> /min	7.0/8.4	7.0/9.1	7.0/9.4	7.0/9.8	9.7/12.2	11.5/14.4	13.5/18.3
Air filter	Type			Washable resin net						
Sound power level	Cooling	At high fan speed	dB(A)	51.0	52.0	53.0	55.0	58.0	63.0	
Sound pressure level	Cooling	Low/High fan speed	dB(A)	28.5/32.0	28.5/33.0	28.5/35.0	28.5/37.5	33.5/37.0	35.5/41.0	38.5/46.5
	Heating	Low/High fan speed	dB(A)	28.5/33.0	28.5/34.0	28.5/36.0	28.5/38.5	33.5/38.0	35.5/42.0	38.5/47.0
Refrigerant	Type/GWP			R-32 / 675						
Piping connections	Liquid	OD	mm	6.35						
	Gas	OD	mm	9.52				12.7		
	Drain			VP13 (I.D. 15/O.D. 18)						
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/220-240						
Current - 50Hz	Maximum fuse amps (MFA)		A	6						
Control systems	Infrared remote control			BRC7EA628 / BRC7EA629 (1)						
	Wired remote control			BRC1H52W/S/K						

(1) Must be combined with Madoka wired remote controller.

\*Note: blue cells contain preliminary data