

Wall mounted unit

FTXTP-A + RXTP-A



comfora



-30°

Guaranteed operation down to -30°C



Energy saving during standby mode



3-D air flow

Wall mounted unit providing high efficiency and comfort down to -30°C

- › Guaranteed heating operation down to -30°C
- › Ideal for above door installation
- › Full range A++
- › 3-D airflow: air is blown into all corners of a room
- › Onecta app
- › Voice control
- › Space saving contemporary wall mounted design
- › Bluevolution range: lower environmental impact

FTXTP-A + RXTP-A



Efficiency data		FTXTP + RXTP		25A + 25A		35A + 35A	
Cooling capacity	Min./Nom./Max.	kW		1/2.5/4.1		1/3.5/4.5	
Heating capacity	Min./Nom./Max.	kW		1/3.2/6.2		1/4/6.7	
Power input	Cooling	Nom.	kW	0.51		0.74	
	Heating	Nom.	kW	0.65		0.88	
Space cooling	Energy efficiency class			A+++			
	Capacity	Pdesign	kW	2.5		3.5	
	SEER			8.55			
Annual energy consumption		kWh/a		102		143	
Space heating (Average climate)	Energy efficiency class			A++			
	Capacity	Pdesign	kW	2.5		3	
	SCOP/A			4.95			
Annual energy consumption		kWh/a		707		866	
Space heating (Cold climate)	Energy efficiency class			A			
	Capacity	Pdesign	kW	3.65		4.38	
	Annual energy consumption			1,937			
SCOP/C				3.96		3.79	
Nominal efficiency	EER			4.88			
	COP			4.99			
	Annual energy consumption			kWh		256	
Energy labeling		Cooling/Heating Directive		A/A			
Current - 50Hz	Maximum fuse amps (MFA)		A	16			


Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for operation range

Indoor unit		FTXTP		25A		35A	
Dimensions	Unit	HeightxWidthxDepth		mm			
Weight	Unit			286 x 770 x 225			
Air filter	Type			Removable / washable			
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/ High	m ³ /min		3.7/5/7.9/11	
		Heating	Silent operation / Low / Medium / High	m ³ /min		4.4 / 5.5 / 9 / 10.5	
Sound power level	Cooling			dBA		58	
	Heating			dBA		58	
Sound pressure level	Cooling	Silent operation/Low/High		dBA		21/26/43	
	Heating	Silent operation/Low/High		dBA		21/26/43	
Control systems	Infrared remote control				ARC480A78		
	Wired remote control				-		

Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m | See separate drawing for electrical data

Outdoor unit		RXTP		25A		35A		
Dimensions	Unit	HeightxWidthxDepth		mm				
Weight	Unit			605 x 930 x 376				
Sound power level	Cooling	Nom.		dBA		60.0		
	Heating	Nom.		dBA		60.0		
Sound pressure level	Cooling	Nom.		dBA		48		
	Heating	Nom.		dBA		49.0		
Operation range	Cooling	Ambient	Min.~Max.	°CDB		-10 ~46		
	Heating	Ambient	Min.~Max.	°CWB		-31 ~18		
				°CDB		-30 ~24		
Refrigerant	Type			R-32				
	GWP			675.0				
	Charge			kg/ tCO ₂ Eq		0.97/0.66		
Piping connections	Liquid	OD		mm		6.35		
	Gas	OD		mm		9.5		
	Piping length	OU - IU	Max.	m		20		
	Additional refrigerant charge				kg/m		0.02 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m		15.0		
Power supply	Phase/Hz/V				1~/50/220-240			
Current - 50Hz	A				16			

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · België · www.daikin.eu · BE 0412 120 336 · RPR Oostende



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN24-065

10/2024



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.