

Floor standing unit

FVXTM-A + RXTM-A



nepura **BLUEEVOLUTION**



Heat boost



Floor warming



Heat plus



Guaranteed operation down to -30°C

Design floor standing unit for optimal heating comfort down to -30°C thanks to unique heating

- › Guaranteed heating capacity down to -30°C
- › Full range A++
- › Heat boost: fast heating during start-up (pair only)
- › Floor warming function optimises convection
- › Heat plus provides 30 minutes cosy heating by simulating radiant heat
- › Daikin Flash Streamer technology: powerful air purification
- › Excellent contemporary design
- › Dual air discharge
- › Onecta app
- › Quiet in operation: down to 19dBA sound pressure level

FVXTM-A + RXTM-A



Indoor unit		FVXTM-A		30A	
Dimensions	Unit	HeightxWidthxDepth		mm	
Weight	Unit			600 x750 x238	
Air filter	Type			Removable / washable	
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/High	m ³ /min	4.0 /4.8 /6.7 /9.0
		Heating	Silent operation / Low / Medium / High	m ³ /min	4.0 / 5.3 / 6.8 / 9.4
Sound power level	Cooling			dBA	
	Heating			dBA	
Sound pressure level	Cooling	Silent operation/Low/High		dBA	
	Heating	Silent operation/Low/High		dBA	
Control systems	Infrared remote control			ARC466A66	
	Wired remote control			BRC073A1	


Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m | See separate drawing for electrical data

Outdoor unit		RXTM		30A	
Dimensions	Unit	HeightxWidthxDepth		mm	
Weight	Unit			kg	
Sound power level	Cooling			dBA	
	Heating			dBA	
Sound pressure level	Cooling	Nom.			dBA
	Heating	Nom.			dBA
Operation range	Cooling	Ambient	Min.~Max.	°CDB	
	Heating	Ambient	Min.~Max.	°CWB	
Refrigerant	Type			R-32	
	GWP			675.0	
	Charge			kg/TCO ₂ Eq	
Piping connections	Liquid	OD			mm
	Gas	OD			mm
	Piping length	OU - IU	Max.	m	
	Additional refrigerant charge			kg/m	
	Level difference	IU - OU	Max.	m	
Power supply	Phase/Frequency/Voltage			Hz/V	
Current - 50Hz	Maximum fuse amps (MFA)			A	

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

Efficiency data		FVXTM-A + RXTM		30A + 30A	
Cooling capacity	Min./Nom./Max.			kW	
Heating capacity	Min./Nom./Max.			kW	
Power input	Cooling	Nom.		kW	
	Heating	Nom.		kW	
Space cooling	Energy efficiency class				A++
	Capacity	Pdesign			kW
	SEER			kWh/a	
Space heating (Average climate)	Energy efficiency class				A++
	Capacity	Pdesign			kW
	SCOP/A			kWh/a	
Space heating (Cold climate)	Energy efficiency class				A+
	Capacity	Pdesign			kW
	SCOP/C			kWh/a	
Nominal efficiency	EER			kWh	
	COP			kWh	
	Annual energy consumption			kWh	
Energy labeling Directive	Energy labeling	Cooling/Heating		A/A	
Current - 50Hz	Maximum fuse amps (MFA)			A	

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



ECPEN23-049

08/2023



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: www.eurovent-certification.com

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.