

Wall mounted unit

Discreet wall mounted unit providing high efficiency and comfort

- › Practically inaudible: the unit runs so quietly, you will almost forget it is there.
- › Onecta app: control your indoor from any location with an app, via your local network or internet.
- › Voice command via Amazon Alexa or Google Assistant to control main functions such as set point, operation mode, fan speed, etc
- › Silver allergen removal and air purifying filter captures allergens such as pollen to ensure a steady supply of clean air
- › 3-D air flow combines vertical and horizontal auto swing to circulate a stream of warm or cool air right to the corners of even large spaces
- › The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation
- › Seasonal efficiency values up to A++ in cooling and heating
- › Space saving contemporary wall mounted design
- › Up to 5 indoor units can be connected to 1 multi outdoor unit; all indoor units are individually controllable and do not need to



be installed in the same room or at the same time. They operate simultaneously within the same heating or cooling mode.

NEW

More details and final information can be found by scanning or clicking the QR codes.



FTXP-N



FTXP-N9



RXP-N



RXP-N9

Efficiency data		FTXP + RXP		20N9 + 20N9	25N9 + 25N9	35N9 + 35N9	50N + 50N	60N + 60N	71N + 71N
Cooling capacity	Min./Nom./Max.	kW		1.3/2.00/2.6	1.3/2.50/3.0	1.3/3.50/4.0	1.7/5.0/6.0	1.7/6.0/7.0	2.3/7.1/7.3
Heating capacity	Min./Nom./Max.	kW		1.30/2.50/3.50	1.30/3.00/4.00	1.30/4.00/4.80	1.7/6.0/7.7	1.7/7.0/8.0	2.3/8.2/9.0
Power input	Cooling	Min./Nom./Max.	kW	0.31/0.54/0.72	0.31/0.67/0.72	0.29/1.08/1.30	0.320/1.385/1.826	0.332/1.824/2.980	0.449/2.689/3.274
	Heating			0.25/0.52/0.95	0.25/0.69/0.95	0.29/0.99/1.29	0.440/1.579/2.356	0.456/1.928/2.787	0.617/2.571/3.306
Space cooling	Energy efficiency class						A+ →		
	Capacity	Pdesign	kW	2.00	2.50	3.50	5.0	6.0	7.1
	SEER				7.20		7.30	6.82	6.20
	Annual energy consumption		kWh/a	97	121	170	240	308	401
Space heating (Average climate)	Energy efficiency class				A++ →			A+ →	
	Capacity	Pdesign	kW	2.20	2.40	2.80	4.60	4.80	6.20
	SCOP/A			4.65	4.61	4.64	4.40	4.10	4.01
	Annual energy consumption		kWh/a	663	728	845	1,463	1,638	2,166
Nominal efficiency	EER			3.75					
	COP			4.77	4.36	4.02	3.80	3.63	3.19
	Annual energy consumption		kWh	270	335	540	693	912	1,345
	Energy labeling Directive Cooling/Heating			A/A				-/-	

Indoor unit		FTXP		20N9	25N9	35N9	50N	60N	71N	
Dimensions	Unit	HeightxWidthxDepth	mm	286x770x225			295x990x263			
Weight	Unit		kg	8.50			9.00			
Air filter	Type			Removable / washable						
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/High	m³/min	4.2/5.6/7.4/9.5	4.2/5.8/7.7/9.7	4.5/6.3/8.3/11.5	8.3/11.5/14.0/16.3	9.2/11.8/14.4/16.8	10.1/11.8/14.4/16.8
		Heating	Silent operation/ Low/Medium/High	m³/min	5.2/6.2/8.1/10.4	5.2/6.4/8.1/10.4	5.3/7.0/9.0/11.5	10.4/11.8/14.4/17.3	11.0/12.4/15.3/17.9	
Sound power level	Cooling		dBA	55			58	59	60	62
	Heating		dBA	55			58	61	62	
Sound pressure level	Cooling	Silent operation/Low/High	dBA	19/25/39	19/26/40	20/27/43	27/34/43	30/36/45	32/37/46	
	Heating	Silent operation/Low/High	dBA	21/28/39	21/28/40	21/29/40	30/38/42	32/40/44	33/41/45	
Control systems	Infrared remote control			ARC480A53						

Outdoor unit		RXP		20N9	25N9	35N9	50N	60N	71N	
Dimensions	Unit	HeightxWidthxDepth	mm	550x740x343			734x870x373			
Weight	Unit		kg	26			26	46.0	50.0	
Sound power level	Cooling		dBA	60			62	61	63	66
Sound pressure level	Cooling	Nom.	dBA	46			48	47	49	52
	Heating	Nom.	dBA	47			48	49		52
Operation range	Cooling	Ambient	Min.~Max.	°CDB			-10~-48			
	Heating	Ambient	Min.~Max.	°CWB			-15~-18			
Refrigerant	Type	R-32								
	GWP			675.0			675			
Piping connections	Charge		kg/TCO2Eq	0.55/0.37		0.70/0.48	0.90/0.61	1.15/0.78		
	Liquid	OD	mm	6.4			6.35			
Power supply	Gas	OD	mm	9.5			12.7			
	Piping length	OU - IU	Max.	m			30			
	Additional refrigerant charge		kg/m	0.02 (for piping length exceeding 10m)						
	Level difference	IU - OU	Max.	m			20			
Current - 50Hz	Phase/Frequency/Voltage	Hz/V		1~/50/220-240						
	Maximum fuse amps (MFA)	A		16			20			

Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for electrical data | See separate drawing for operation range | Contains fluorinated greenhouse gases

* Integrated for 20-25-35 class. Standard for 50-60-71 class